

TRACKED MINITRANSPORTER WITH FARM BODY AND HYDRAULIC WINCH

MODEL

954.AMTI-5.0CV-

Hydraulic winch with farm body with removable and/or extensible sides, for the collection and transport of lumber in mountain regions.

<u>Facility to install the winch on several other</u> <u>applications in the 954BBT range</u>

MACHINE DIMENSIONS		
Max height	119 cm	
Max width	76 cm	
Max length (operator platform closed)	213 cm	
Tracks	180 x 60 x 38 mm	
Track width	74 cm	

WEIGHTS	
Payload	500 kg
Payload on gradients in excess of 30%	350 kg
Dry weight	441 kg



TRANSMISSION	
Туре	Hydraulic
Speed	Slow 2.1 km/h Fast 4.8 km/h
Tipping	Hydraulic
Max pressure	160 bar

WINCH SPECIFICATIONS		
Brand	VIME	
Rope diameter	8 mm	
Rope length	25 m	
Winding speed	10.05 rpm	
Horizontal pulling capacity	1st layer 4m	1100kg
	2nd layer 9.7m	930kg
	3rd layer 16.2m	810kg
	4th layer 25m	715kg

E-mail: info@954bbt.com Web: www.954bbt.com

POWER UNITS	HORSEPOWER	CODE
Honda petrol engine with manual/electric starting	9 hp	G09H/GE09H
Axo petrol engine with manual/electric starting	9 hp	G09/GE09
Axo diesel engine with manual/electric starting	7 hp	D07/DE07
Yanmar diesel engine with manual/electric starting	7 hp	D07Y/DE07Y
MYT100 Electric motor, 230 V power supply	3 kW	MYT100