



TRACKED MINI TRANSPORTER COMPATIBLE WITH ALL APPLICATIONS

MODEL 954.AMTI-5.0-

Tracked Minitransporter (undercarriage) with powder-coated steel frame; compatible with all applications in the 954BBT range.
Drive controls on the lh side and actuator levers on the rh side make loading and unloading tasks practical and functional.
Supplied: galvanized steel operator platform with anti-vibration mounts, 2 pairs of ¼" quick couplers and hydraulic dumping cylinder



MACHINE DIMENSIONS

Max height	119 cm
Max width	74 cm
Max length (operator platform closed)	147 cm
Tracks	180 x 60 x 38 mm
Track width	74 cm

WEIGHTS

Overall weight	320 kg

TRANSMISSION

Type	Hydraulic
Speed	Slow 2.1 km/h Fast 4.8 km/h
Tipping	Hydraulic
Max pressure	160 bar

HYDRAULIC SYSTEM

Directional control valves	no.2 Walvoil
Pump	Casappa 4+4
Orbital motors M+S 200	no.2 M+S 200

POWER UNITS	HORSEPOWER	CODE
-------------	------------	------

Honda petrol engine with manual/electric starting	9 hp	G09H/GE09H
Axo petrol engine with manual/electric starting	9 hp	G09/GE09
Axo diesel engine with manual/electric starting	7 hp	D07/DE07
Yanmar diesel engine with manual/electric starting	7 hp	D07Y/DE07Y
MYT100 Electric motor, 230 V power supply	3 kW	MYT100